

Marmaris

Tuft gauge	1/10 loop pile		ISO 2424
Pilecomposition	100% PA SDN		ISO 2424
Primary Backing	Non Woven		ISO 2424
Secondary backing	Bitumen		ISO 2424
Width	50 x 50 cm	± 0,2%	EN 984
Pile Weight	690 gr/m ²		ISO 8543
Total weight	Bitumen : 4425 gr/m ²	± 15%	ISO 8543
Pile height	3 mm	± 2 mm	ISO 1766
Total Height	Bitumen : 6 mm		ISO 1765
Number of knots	240.379/m ²	-7.5% .+10%	ISO 1763
Fire Classification	Bfl-S1		EN 13501-1
Use Area	Heavy project use (33)		EN 1307
Evaluated sound absorptions grade αW	0,15 αW		ISO 11654
Sound Insulation	Ca. 25 dB		ISO 10140
Thermal resistance	Ca. 0,0639 M ² KW		ISO 8302
Light fastness	≥ 5		105-B02
Wearebility	≥ 4		105-X12
Water fastness	≥ 4		105-E01
Electrostatic charging	<2 kV		ISO 6356
Luxury class	LC3		EN 1307
Comments	Installation designs; Monolithic, Quarter turn, Brick, Ashlar, Random.		
Pictures	www.condorcontract.com		

Floorsymbols



Certificates



2021

Condor Carpets
Euroweg 3
8061 SB Hasselt

EN1307

DOP: C-022RBM172

Reaction to fire:
Bfl-s1

Slip resistance: DS

Bitumen

Resilient floor
covering to be
used within a
building

