

Vermont

Tuft gauge	5/32 cut pile	ISO 2424
Pilecomposition	100% PES	ISO 2424
Primary Backing	Woven	ISO 2424
Secondary backing	AB, Felt	ISO 2424
Width	400 cm, 500 cm ± 1%	EN 984
Pile Weight	1100 gr/m ²	ISO 8543
Total weight	AB : 2000 gr/m ² Felt : 2100 gr/m ² ± 15%	ISO 8543
Pile height	12 mm ± 2 mm	ISO 1766
Total Height	AB : 14 mm Felt : 15 mm	ISO 1765
Number of knots	73080/m ² -7.5% .+10%	ISO 1763
Fire Classification	Cfl-S1	EN 13501-1
Use Area	Medium domestic use (22)	EN 1307
GUT Nr.	2911D8AB GUT	www.pro-dis.info
Light fastness	≥ 5	105-B02
Wearebility	≥ 4	105-X12
Water fastness	≥ 4	105-E01

Floorsymbols



Certificates

 2021 Condor Carpets Euroweg 3 8061 SB Hasselt EN1307 DOP: C-025AJ055 Reaction to fire: Cfl-s1 1658 Slip resistance: DS AB Resilient floor covering to be used within a building	 2021 Condor Carpets Euroweg 3 8061 SB Hasselt EN1307 DOP: C-025FJ055 Reaction to fire: Cfl-s1 1658 Slip resistance: DS Felt Resilient floor covering to be used within a building
--	--

